

Frame fixing SXR⁴⁾

Highest permissible loads¹⁾ for a single anchor for multiple fixings of non-structural applications in masonry.

For the design the complete approval ETA-07/0121 has to be considered.

					Solid brick masonry and perforated brick masonry		
Type	compressive brick strength f_b [N/mm ²]	brick type, naming acc. DIN [-] [-]	min. anchorage depth h_{nom} [mm]	min. member thickness h_{min} [mm]	permissible load F_{perm} ³⁾⁵⁾ [kN]	min. spacing s_{min} ²⁾ [mm]	min. edge distance c_{min} ²⁾ [mm]
Solid brick Mz							
SXR 8	≥ 20	Mz	50	100	0,71	100	100
SXR 10	≥ 20	Mz	50	100	0,86	100	100
Solid sand-lime brick and solid block KS							
SXR 8	≥ 10	KS	50	100	0,71	100	100
SXR 10	≥ 10	KS	50	100	0,86	100	100
Vertically perforated brick HLz							
SXR 8	≥ 20	HLz	50	100	0,34	100	100
SXR 10	≥ 12	HLz	50	100	0,26	100	100
SXR 10	≥ 20	HLz	50	100	0,71	100	100
Perforated sand-lime brick KSL							
SXR 8	≥ 12	KSL	50	100	0,57	100	100
SXR 10	≥ 12	KSL	50	100	0,57	100	100
Hollow block of lightweight aggregate concrete Hbl							
SXR 8	≥ 10	Hbl	50	100	0,71	100	100
SXR 10	≥ 6	Hbl	50	100	0,71	100	100
SXR 10	≥ 10	Hbl	50	100	0,71	100	100
Solid brick and solid block of lightweight aggregate concrete V							
SXR 8	≥ 2	V	50	100	0,34	100	100
SXR 10	≥ 2	V	50	100	0,21	100	100
Aerated concrete blocks and reinforced panels AAC							
SXR 10	≥ 2	AAC	50	100	0,14 ⁷⁾	200	100
SXR 10	≥ 6	AAC	50	100	0,27	200	100

¹⁾ The required partial safety factors for material resistance as well as a partial safety factor for load actions $\gamma_L = 1,4$ are considered. As a single anchor counts e.g. an anchor with a minimum spacing s_{min} according table 11 resp. table 15 of the approval.

²⁾ Minimum possible axial spacings (anchor group) resp. edge distance while reducing the permissible load. The combination of the given min. spacing and min. edge distance is not possible. One of them has to be increased according approval.

³⁾ Valid for tensile load, shear load and oblique load under any angle. For combinations of tensile loads, shear loads and bending moments see approval.

⁴⁾ Valid for zinc coated screws and for screws made of stainless steel. For exterior use of the zinc coated screws measures against incoming humidity according approval have to be taken.

⁵⁾ The given values for hollow or perforated masonry apply for rotary drilling (without impact). The given loads are reference values which may change due to type of brick and manufacturer. If the embedment depth is higher than $h_{nom} = 50$ mm, job site tests have to be carried out.

⁶⁾ Valid for temperatures in the substrate up to +50 °C (resp. short term up to 80 °C). For long term temperatures up to 30 °C higher permissible loads may be possible.

⁷⁾ Drill hole created by punching.

LOADS

Frame fixing SXR ⁴⁾

Highest permissible loads ^{1) 6)} for a single anchor for multiple fixings of non-structural applications in normal concrete \geq C12/15 resp. \geq B15. For the design the complete approval ETA-07/0121 has to be considered.

Type	Cracked or Non-cracked concrete					
	Min. anchorage depth	Min. member thickness	Permissible tensile load	Permissible shear load	Min. spacing	Min. edge distance
	h_{nom} [mm]	h_{min} [mm]	$N_{perm}^{3)}$ [kN]	$V_{perm}^{3)}$	$s_{min}^{2)}$ [mm]	$c_{min}^{2)}$ [mm]
SXR 8	50	100	1,0	1,2 ⁵⁾	50	50
SXR 10	50	100	1,8	2,0 ⁵⁾	50	60

¹⁾ The required partial safety factors for material resistance as well as a partial safety factor for load actions $\gamma_L = 1,4$ are considered. As a single anchor counts e.g. an anchor with a spacing $s \geq s_{cr,N}$ and an edge distance $c \geq c_{cr,N}$ according table 8 of the approval.

²⁾ Minimum possible axial spacings (anchor group) resp. edge distance for concrete \geq C16/20 while reducing the permissible load. The combination of the given min. spacing and min. edge distance is not possible. One of them has to be increased according approval. Values for concrete C12/15 see approval.

³⁾ For combinations of tensile loads, shear loads, bending moments as well as reduced edge distances or spacings (anchor groups) see approval.

⁴⁾ Valid for zinc coated screws and for screws made of stainless steel. For exterior use of the zinc coated screws measures against incoming humidity according approval have to be taken.

⁵⁾ The permissible shear load determined acc. ETAG 020, Annex C considers exclusively steel failure of the screw. For SXR 8 it amounts $V_{perm} = 4,2$ kN for galvanised screws and $V_{perm} = 3,4$ kN for screws made of stainless steel. For SXR 10 it amounts $V_{perm} = 6,0$ kN. Due to that the expected displacements will disable the proper function of the fixture a maximum shear load on the basis of table 7 of the approval is recommended.

⁶⁾ Valid for temperatures in the substrate up to +50 °C (resp. short term up to 80 °C). For long term temperatures up to 30 °C higher permissible loads may be possible.

LOADS

Frame fixing SXR

Highest recommended loads ¹⁾ for a single anchor.

The given loads are valid for wood screws with the specified diameter.

Type	SXR 6		
Screw diameter	\emptyset	[mm]	4,5
Min. edge distance in concrete	a_r	[mm]	50
Recommended loads in the respective base material $F_{rec}^{2)}$			
Concrete	\geq C20/25	[kN]	0,25
Solid brick	\geq Mz 12	[kN]	0,20
Solid sand-lime brick	\geq KS 12	[kN]	0,20
Vertically perforated brick	\geq Hlz 12 ($\rho \geq 1.0$ kg/dm ³)	[kN]	0,10
Perforated sand-lime brick	\geq KSL 12	[kN]	0,20

¹⁾ Required safety factors are considered.

²⁾ Valid for tensile load, shear load and oblique load under any angle.