

Bedrijvenpark Twente 193 NL-702 KG Almelo – The Netherlands

Tel: +31 (0)546 - 572 672 Mail: info@berdal.com

		the European Commission)
Unique identification code of product-type	Pandser EPDM thickness 1.00, 1.14, 1.20, 1.50, 2.00 mm, BRD011	
Intended use/uses	Roofsheets for the application of waterproofing roofs in buildings. Application in single-ply roofing systems	
Manufacturer	Berdal Rubber & Plastics BV Bedrijvenpark Twente 193 7602 KG Almelo – The Netherlands	
Authorised representative	Not applicable	
The system or systems for assesssing and verifying performance resistance (AVCP)	AVCP 2+	
Harmonised standard	EN 13956:2013	
Notified authority	AENOR, Notification nr. 0099. Ref. Certificate of conformance A85/0044	
7. Declared performance (s)	Essential features:	Performances:
	Fire reaction	Classe E
	External fire performance	Broof (t1)
	Waterimpermeability:	'Pass' at 60 kPa
	Tensile strength	≥ 9.0 MPa
	Resistance to impact	≥ 200 mm
	Elongation at break	≥ 300%
		≥ 25 kg
		≥ 20 N
	_	
	P ·	≥ 200 N/50 mm
	- Peel resistance	≥ 25 N/50 mm
	Durability regarding to:	Doco
	,	Pass
	- UV resistance - artificial ageing (2 kPa)	Pass Pass
	(model in accordance with delegation code of product-type Intended use/uses Manufacturer Authorised representative The system or systems for assesssing and verifying performance resistance (AVCP) Harmonised standard Notified authority	Unique identification code of product-type Intended use/uses Roofsheets for the application Application in single-ply roofin Application in single-ply roofin Berdal Rubber & Plastics BV Bedrijvenpark Twente 193 7602 KG Almelo – The Netherl Not applicable The system or systems for assesssing and verifying performance resistance (AVCP) Harmonised standard Notified authority AENOR, Notification nr. 0099. A85/0044 Declared performance (s) Essential features: Fire reaction External fire performance Waterimpermeability: Tensile strength Resistance to impact Elongation at break Resistance to static load Tear resistance Adhesion strengths - Tensile/shear resistance - Peel resistance Durability regarding to: - waterimpermeability - UV resistance

The performance of the product identified is in comformity with the set of declared performance/s. This declaration of performance is issued in accordance with (UE) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer.

B.M.D. van Kamperdijk, General Manager

Almelo, The Netherlands, 1 March 2018

Bedrijvenpark Twente 193 7602 KG Almelo +31(0)546-572672

www.berdal.com