

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 1 of 14

Print date: 25/03/2021

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: PANDSER® BONDING ADHESIVE

1.2 Relevant identified uses of the substance or mixture and uses advised against.

INDUSTRIAL AND PROFESSIONAL ADHESIVE

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **BERDAL Rubber & Plastics B.V.**
Address: Bedrijvenpark Twente 193, 7602 KG
City: Almelo
Telephone: +31 546 572 672
Fax: +31 546 575 635
E-mail: sales@berdal.com
Web: www.berdal.com

1.4 Emergency telephone number: +44 111

CODE UFI: DHRC-YHAT-461M-QCDY

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation.

Flam. Liq. 2 : Highly flammable liquid and vapour.

Repr. 2 : Suspected of damaging fertility or the unborn child.

STOT RE 2 : May cause damage to organs through prolonged or repeated exposure.

STOT SE 3 : May cause drowsiness or dizziness.

Skin Irrit. 2 : Causes skin irritation.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

P statements:

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 2 of 14

Print date: 25/03/2021

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P370+P378	In case of fire: Use CO ₂ , chemical foam or dusty. Never use water.

Contains:

toluene

acetone, propan-2-one, propanone

ethyl acetate

Hydrocarbons, C₇, n-alkanes, isoalkanes, cyclics

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 601-021-00-3 CAS No: 108-88-3 EC No: 203-625-9 Registration No: 01-2119471310-51-XXXX	[1] toluene	20 - 25 %	Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Repr. 2, H361d *** - STOT RE 2 *, H373 ** - STOT SE 3, H336 - Skin Irrit. 2, H315	-
CAS No: 64742-49-0 Registration No: 01-2119475515-33-XXXX	Hydrocarbons, C ₇ , n-alkanes, isoalkanes, cyclics	10 - 20 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT SE 3, H336 - Skin Irrit. 2, H315	-
Index No: 606-001-00-8 CAS No: 67-64-1 EC No: 200-662-2 Registration No: 01-2119471330-49-XXXX	[1] acetone, propan-2-one, propanone	1 - 10 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 607-022-00-5 CAS No: 141-78-6 EC No: 205-500-4 Registration No: 01-2119475103-46-XXXX	[1] ethyl acetate	1 - 10 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 3 of 14

Print date: 25/03/2021

Index No: 601-022-00-9 CAS No: 95-47-6 EC No: 202-422-2 Registration No: 01-2119488216-32-XXXX	[1] o-xylene	1 - 10 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
---	--------------	----------	---	---

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

*, **, *** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Long-term chronic exposure may result in injury to certain organs or tissues.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019
Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 4 of 14
Print date: 25/03/2021

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

7.3 Specific end use(s).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



PANDSER® BONDING ADHESIVE

Version 1 Date of compilation: 14/10/2019
Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 5 of 14
Print date: 25/03/2021

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
toluene	108-88-3	European Union [1]	Eight hours	50 (skin)	192 (skin)
			Short term	100 (skin)	384 (skin)
		United Kingdom [2]	Eight hours	50	191
			Short term	100	384
		Éire [3]	Eight hours	50	192
			Short term	100	384
		United States [4] (Cal/OSHA)	Eight hours	10	
			Short term	150 (Ceiling) 500	
		United States [5] (NIOSH)	Eight hours	100	
			Short term	150	
United States [6] (OSHA)	Eight hours	200			
	Short term	300 Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 500 [10 min]			
acetone, propan-2-one, propanone	67-64-1	European Union [1]	Eight hours	500	1210
			Short term		
		United Kingdom [2]	Eight hours	500	1210
			Short term	1500	3620
		Éire [3]	Eight hours	500	1210
			Short term		
		United States [4] (Cal/OSHA)	Eight hours	500	
			Short term	750 (Ceiling) 3000	
		United States [5] (NIOSH)	Eight hours	250	
			Short term		
United States [6] (OSHA)	Eight hours	1000	2400		
	Short term				
ethyl acetate	141-78-6	European Union [1]	Eight hours	200	734
			Short term	400	1468
		United Kingdom [2]	Eight hours	200	
			Short term	400	
		Éire [3]	Eight hours	200	734
			Short term	400	1468
		United States [4] (Cal/OSHA)	Eight hours	400	
			Short term		
		United States [5] (NIOSH)	Eight hours	400	
			Short term		
United States [6] (OSHA)	Eight hours	400	1400		
	Short term				
o-xylene	95-47-6	European Union [1]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)
		Éire [3]	Eight hours	50	221
			Short term	100	442

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



PANDSER® BONDING ADHESIVE

Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 6 of 14

Print date: 25/03/2021

[3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
toluene CAS No: 108-88-3 EC No: 203-625-9	DNEL (Workers)	Inhalation, Long-term, Local effects	192 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	192 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Systemic effects	384 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Systemic effects	226 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	384 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Local effects	226 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	384 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	226 (mg/kg bw/day)
acetone, propan-2-one, propanone CAS No: 67-64-1 EC No: 200-662-2	DNEL (Workers)	Inhalation, Long-term, Systemic effects	1210 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	200 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	2420 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	186 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	62 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	62 (mg/kg bw/day)
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	734 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Local effects	734 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	367 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	1468 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Local effects	734 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	63 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	37 (mg/kg bw/day)
o-xylene CAS No: 95-47-6	DNEL (Workers)	Inhalation, Long-term, Local effects	221 (mg/m ³)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 7 of 14

Print date: 25/03/2021

EC No: 202-422-2	DNEL (Workers)	Inhalation, Long-term, Systemic effects	221 (mg/m ³)
------------------	-------------------	---	-----------------------------

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
Concentration levels PNEC:

Name	Details	Value
toluene CAS No: 108-88-3 EC No: 203-625-9	aqua (freshwater)	0,68 (mg/L)
	aqua (marine water)	0,68 (mg/L)
	aqua (intermittent releases)	0,68 (mg/L)
	STP	13,61 (mg/L)
	sediment (freshwater)	16,39 (mg/kg sediment dw)
	sediment (marine water)	16,39 (mg/kg sediment dw)
acetone, propan-2-one, propanone CAS No: 67-64-1 EC No: 200-662-2	aqua (freshwater)	10,6 (mg/L)
	aqua (marine water)	1,06 (mg/L)
	aqua (intermittent releases)	21 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	30,04 (mg/kg sediment dw)
	sediment (marine water)	3,04 (mg/kg sediment dw)
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	soil	29,5 (mg/kg soil dw)
	aqua (freshwater)	0,24 (mg/L)
	aqua (marine water)	0,024 (mg/L)
	aqua (intermittent releases)	1,65 (mg/L)
	sediment (freshwater)	1,15 (mg/L)
	sediment (marine water)	0,115 (mg/L)
	Soil	0,148 (mg/kg soil dw)
	STP	650 (mg/L)
oral (Hazard for predators)	0,2 (g/kg food)	

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %	
Uses:	INDUSTRIAL AND PROFESSIONAL ADHESIVE	
Breathing protection:		
PPE:	Filter mask for protection against gases and particles.	
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.	
CEN standards:	EN 136, EN 140, EN 405	
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.	
Observations:		
Filter Type needed:	A2	
Hand protection:		
PPE:	Protective gloves against chemicals.	
Characteristics:	«CE» marking, category III.	
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420	

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 8 of 14

Print date: 25/03/2021

Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Anti-static safety footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346		
Maintenance:	The footwear should be checked regularly		
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour and colour

Colour: Ambar

Odour: ORGANIC SOLVENT

Odour threshold: N.A./N.A.

pH: N.A./N.A.

Melting point: N.A./N.A.

Boiling Point: 82 °C

Flash point: 1 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: 91

Vapour density: N.A./N.A.

Relative density: 0.80 ± 0.02

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 9 of 14

Print date: 25/03/2021

9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
toluene CAS No: 108-88-3 EC No: 203-625-9	Oral			
	Dermal	LD50	Rabbit	12200 mg/kg bw [1]
				[1] American Industrial Hygiene Association Journal. Vol. 30, Pg. 470, 1969
acetone, propan-2-one, propanone CAS No: 67-64-1 EC No: 200-662-2	Inhalation	LC50	Rat	49 mg/l/4 h [1]
	Oral			
		LD50	Rat	5800 mg/kg bw [1]
			[1] Journal of Toxicology and Environmental Health. Vol. 15, Pg. 609, 1985	
	Dermal			
	Inhalation			

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 10 of 14

Print date: 25/03/2021

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 36.667 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Product classified:

Reproductive toxicant, Category 2: Suspected of damaging fertility or the unborn child.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;

Product classified:

Specific target organ toxicity following a repeated exposure, Category 2: May cause damage to organs through prolonged or repeated exposure.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
toluene	Fish	LC50	Fish	31,7 mg/l (96 h) [1]
				[1] Geiger, D.L., L.T. Brooke, and D.J. Call 1990. Acute Toxicities of Organic Chemicals to Fathead Minnows (<i>Pimephales promelas</i>), Volume 5. Ctr.for Lake Superior Environ.Stud., Univ.of Wisconsin-Superior, Superior, WI :332 p
	Aquatic invertebrates	LC50	Crustacean	92 mg/l (48 h) [1]
			[1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to <i>Daphnia magna</i> and <i>Artemia</i> . Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p	
	Aquatic plants	EC50	Algae	12,5 mg/l (72 h) [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 11 of 14

Print date: 25/03/2021

CAS No: 108-88-3 EC No: 203-625-9		[1] Galassi, S., M. Mingazzini, L. Vigano, D. Cesareo, and M.L.Tosato 1988. Approaches to Modeling Toxic Responses of Aquatic Organisms to Aromatic Hydrocarbons. Ecotoxicol.Environ.Saf. 16(2):158-169
acetone, propan-2-one, propanone	Fish	LC50 Fish 8300 mg/l (96 h) [1] [1] Cairns, J.Jr., and A. Scheier 1968. A Comparison of the Toxicity of Some Common Industrial Waste Components Tested Individually and Combined. Prog.Fish-Cult. 30(1):3-8
	Aquatic invertebrates	LC50 Crustacean 8450 mg/l (48 h) [1] [1] Cowgill, U.M., and D.P. Milazzo 1991. The Sensitivity of Ceriodaphnia dubia and Daphnia magna to Seven Chemicals Utilizing the Three-Brood Test. Arch.Environ.Contam.Toxicol. 20(2):211-217. Canton, J.H., and D.M.M. Adema 1978. Reproducibility of Short-Term and Reproduction Toxicity Experiments with Daphnia magna and Comparison of the Sensitivity of Daphnia magna with Daphnia pulex and Daphnia cucullata in Short-Term Experiments. Hydrobiologia 59(2):135-140 (Used Reference 2018)
	Aquatic plants	EC50 Algae 7200 mg/l (96 h) [1] [1] Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl.Tech.Inf.Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)
CAS No: 67-64-1 EC No: 200-662-2		

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
toluene CAS No: 108-88-3 EC No: 203-625-9	2,73	-	-	Low
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	0,73	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 12 of 14

Print date: 25/03/2021

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number.

UN No: UN1133

14.2 UN proper shipping name.

Description:

ADR: UN 1133, ADHESIVES, 3, PG II, (D/E)

IMDG: UN 1133, ADHESIVES, 3, PG II (1°C)

ICAO/IATA: UN 1133, ADHESIVES, 3, PG II

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 3



Hazard number: 33

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-D

Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 13 of 14

Print date: 25/03/2021

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 59,256 %

VOC content: 474,05 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5b

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
48. Toluene CAS No 108-88-3 EC No 203-625-9	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Kind of pollutant to water (Germany): WGK 2: Hazardous to water. (Autoclassified according to the AwSV Regulations)

iError! Nombre de archivo no válido.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Available Product Exposure Scenario.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4

Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2

Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3

Asp. Tox. 1 : Aspiration toxicity, Category 1

Eye Irrit. 2 : Eye irritation, Category 2

Flam. Liq. 2 : Flammable liquid, Category 2

Flam. Liq. 3 : Flammable liquid, Category 3

Repr. 2 : Reproductive toxicant, Category 2

STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2

STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Skin Irrit. 2 : Skin irritant, Category 2

Changes regarding to the previous version:

- Modification in the values of the physical and chemical properties (SECTION 9).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

PANDSER® BONDING ADHESIVE



Version 1 Date of compilation: 14/10/2019

Version 19 (replaces version 18)

Revision date: 22/03/2021

Page 14 of 14

Print date: 25/03/2021

- Change in the hazard classification (SECTION 11.1).
- National legislative changes (SECTION 15.1).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC)

1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Available Product Exposure Scenario.

Abbreviations and acronyms used:

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
AWSV:	Facility Regulations for handling substances that are hazardous for the water.
BCF:	Bioconcentration factor.
CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50:	Half maximal effective concentration.
PPE:	Personal protection equipment.
IATA:	International Air Transport Association.
ICAO:	International Civil Aviation Organization.
IMDG:	International Maritime Code for Dangerous Goods.
LC50:	Lethal concentration, 50%.
LD50:	Lethal dose, 50%.
Log Pow:	Logarithm of the partition octanol-water.
NOEC:	No observed effect concentration.
PNEC:	Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID:	Regulations Concerning the International Transport of Dangerous Goods by Rail.
WGK:	Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.