

# LOADS

## High performance anchor FH II - H

**Highest permissible loads for a single anchor**<sup>1)</sup> in concrete C20/25<sup>4)</sup>

For the design the complete approval ETA - 07/0025 has to be considered.

				Cracked concrete				Non-cracked concrete			
Type	Effective anchorage depth $h_{ef}$ [mm]	Min. member thickness $h_{min}$ [mm]	Installation torque $T_{inst}$ [Nm]	Permissible tensile load $N_{perm}$ <sup>3)</sup> [kN]	Permissible shear load $V_{perm}$ <sup>3)</sup> [kN]	Min. spacing $s_{min}$ <sup>2)</sup> [mm]	Min. edge distance $c_{min}$ <sup>2)</sup> [mm]	Permissible tensile load $N_{perm}$ <sup>3)</sup> [kN]	Permissible shear load $V_{perm}$ <sup>3)</sup> [kN]	Min. spacing $s_{min}$ <sup>2)</sup> [mm]	Min. edge distance $c_{min}$ <sup>2)</sup> [mm]
<b>FH II 10 H</b>	40	80	10,0	3,6	4,3	40	40	6,1	6,1	40	40
<b>FH II 12 H</b>	60	120	22,5	5,7	15,4	50	50	11,2	15,4	60	60
<b>FH II 15 H</b>	70	140	40,0	7,6	20,1	60	60	14,1	23,4	70	70
<b>FH II 18 H</b>	80	160	80,0	11,9	24,5	70	70	17,2	34,4	80	80

<sup>1)</sup> The partial safety factors for material resistance as regulated in the approval as well as a partial safety factor for load actions of  $\gamma_L = 1,4$  are considered. As an single anchor counts e.g. an anchor with a spacing  $s \geq 3 \times h_{ef}$  and an edge distance  $c \geq 1,5 \times h_{ef}$ . Accurate data see approval.

<sup>2)</sup> Minimum possible axial spacings resp. edge distance while reducing the permissible load.

<sup>3)</sup> For combinations of tensile loads, shear loads, bending moments as well as reduced edge distances or spacings (anchor groups) see approval.

<sup>4)</sup> For higher concrete strength classes up to C50/60 higher permissible loads may be possible.