

EU Type Examination Certificate

Date: 2018/08/08

n. **158183201/OE**

Validity:
2023/08/07

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	GRISPORT SpA calzaturificio 31030 CASTELCUCCO (TV) – Via Erega, 1 – ITALIA
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)
Category of PPE:	II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.
Model	"701619CP40"
Description:	<p><u>model</u>: B (ankle boot); <u>fastening system</u>: by means of laces; <u>processing</u>: direct injection; <u>outsole</u>: grey rubber with an orange insert marked "TOTAL GRIP HI SRC HRO CROSS OIL RESISTANT" (030EBN/00 – 003/ 32E/00);</p> <p><u>midsole</u>: black foam PU (MPI/001);</p> <p><u>upper</u>: black fabric POLY600 7mm matched with GARBOFORT (P6G/NER), with lateral inserts made of coated non-woven fabric declared thickness 1,4 mm LAV. EST. col. TRUE BLACK (PRE/TRBL) and, in the heel area, inserts made of coated non-woven fabric declared thickness 1,4 mm SINTETICO col. TRUE BLACK (PRB/TRBL);</p> <p><u>tongue</u>: simple black fabric POLY600 7mm (P6G/NER);</p> <p><u>bellows</u>: black coated fabric art. ANDREA SILVIA (ANS/NER) lined;</p> <p><u>vamp lining</u>: black non-woven fabric ATELLE 150 matched with MTP4 D40 and black CHARMEUSE (FCA/NEC);</p> <p><u>rear lining</u>: three-dimensional fabric AT 488 SPECIAL col. ice (A8S/91);</p> <p><u>heel-grip</u>: dark grey microfiber MICROLIM 0,8 SCAMOSCINA (MI8/NER);</p> <p><u>insole</u>: multilayered white fabric ZP02/1500 (LC/ZP02) <u>which also serves as penetration resistant insert</u>;</p> <p><u>removable insock</u>: grey foam perforated material matched with black fabric in contact with the user, with an aluminum oval stitched with antistatic thread in the lower part of the foot sole, with an insert made of ABS col. red in the heel area (FTNAROA); as an alternative to <u>removable insock</u>: agglomerated black fabric with a reinforcement made of red foam fabric in the heel area, matched with black/silver fabric in contact with the user (article FM126N);</p> <p><u>toe-cap</u>: made of glass fiber art. 604 CONTENDER (604FV); as an alternative to <u>toe-cap</u>: made of glass fiber art. 604 SAFIT (604FV).</p> <p><u>Optional interchangeable orthopedic insocks (DGUV 112-191)</u> described by the Customer as below (see also page 2): SECOSOL® by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 2,93 mm)</p> <p>A) Secosol BASE 9516 incl. EVA-covers Sizes: 35/50 (95161001114100-95164294249459)</p> <p>B) Secosol BASE 9516 incl. TEXTIL-covers Sizes: 35/50 (95161001114100-95164294249459)</p> <p>C) Secosol Complete incl. EVA-covers Sizes: 35/36 – 49/50 (95162201245136 – 95162201245150)</p> <p>D) Secosol Complete incl. TEXTIL-covers Sizes: 35/36 – 49/50 (95162201247136 – 95162201247150).</p>
Technical Standard:	<p>EN ISO 20344:2011 (UNI EN ISO 20344:2012)</p> <p>EN ISO 20345:2011 (UNI EN ISO 20345:2012)</p> <p>Personal protective equipment – Test methods for footwear</p> <p>Personal protective equipment – Safety footwear</p>

EU Type Examination Certificate

Date: 2018/08/08

n. **158183201/OE**

Validity:
2023/08/07

Intended use:	general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.
Size range:	from 35 to 48
Technical File:	DC-9636/E
Test report:	RCT n°3727072/E
Functions and performance levels:	<p>basic requirements for safety footwear (SB) (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:</p> <p>SRC = Slip resistance – meets the following requirement: - <u>surface</u>: ceramic / <u>lubricant</u>: detergent solution; - <u>surface</u>: steel / <u>lubricant</u>: glycerol.</p> <p>Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011): S3 = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; HRO = resistance to hot contact of the outsole; HI = heat insulation of sole complex.</p> <p>Note 1: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption). Note 2: the footwear also meets the requirement in accordance with IEC 61340-5-1:2016 (IEC 61340-4-3:2001) for the electrical resistance ESD class 1 (electric dissipative footwear).</p>

Marking:



on a stitched label and displaying the following information:

- **CE Marking**;
- Name of the Manufacturer (on the external side of the footwear);
- designation of the footwear (article code: unique/unambiguous);
- nr. and year of the Standard of reference;
- safety symbols;
- size of the footwear;
- production date (month + year);
- additional information: internal codes.



A) Secosol BASE 9516
incl. EVA-covers
Sizes: 35/50
(95161001114100-
95164294249459)

B) Secosol BASE 9516
incl. TEXTIL-covers
Sizes: 35/50
(95161001114100-
95164294249459)

C) Secosol Complete
incl. EVA-covers
Sizes: 35/36 – 49/50
(95162201245136-
95162201245150)

D) Secosol Complete
incl. TEXTIL-covers
Sizes: 35/36 – 49/50
(95162201247136-
95162201247150)

NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

